



Basic Paint-cleaner

(Ambruch 2 / Viscosol)

Tested and recommended by Qualicare and GRM/Germany.

Applicable for:

For cleaning and preservation of all surfaces made of coated Aluminium and plastics. Not suitable for one layer metallic lacquers.

Composition and characteristics:

Basic Paint-cleaner is a cleaner and preservative in one. Contains care compounds, polishing compounds and preservatives. Quick and easy to use, economic and high efficiency.

Instructions for use:

Essential – always carry out a test first!

Shake well before using. Do not use on hot or wet surfaces. No warranty for incorrect use.

New, slightly soiled surfaces:

Apply a thin layer using a soft soaked cloth. Allow to dry for a few seconds. Polish after short while using a clean, soft cloth. Produces a shiny, waterproof, thin layer.

Medium soiled surfaces:

Apply onto cleaning pad (white) and brush evenly with medium pressure. Remove dissolved soiling with a soft cloth. If necessary repeat until all soiling and stains are removed. Then polish with a new, soft cloth for even appearance.

Heavily soiled, chalking surfaces:

Carry out basic cleaning with use of Abrasive Paint-additive and Cleaning Pad (white) for more abrasion. The Paint-additive and all detergent residues must be removed completely by washing down and flushing with fresh water before polishing.

Safety information:

Flammable. Avoid open flames. Harmful. Store in cool, dry place

Class 3 PG. III UN 1993 VbF: A II

Harmful, contains Aliphatic Hydrocarbons and Isopropanol

Rudolf Ambruch
Fassadenpflege GmbH
Esperantostr.12,
D- 70197 Stuttgart/ Germany

Phone: +49- 711- 6599 319
Fax: +49- 711- 6599 320
mail: Ambruch@t-online.de